

# Quality Assurance 'LUNA' Tool for Many Point Experiments

Martin Burk

June 25, 2014

This work was done by National Security Technologies, LLC  
Under Contract No. DE-AC52-06NA25946  
With the U.S. Department of Energy.



**Nevada National Security Site**

*Managed and Operated by National Security Technologies, LLC*



## What is the problem?

- To many channels to little time to tune, setup, verify 128 channels or 256 channels.
- Need to check integrity of the entire fiber path with little or no disruption to any connections.
- Ability to characterize the fiber path for proper connections, return loss calculations, and indication of return power from the surface.
- Ability to check and verify for movement between the probe and surface during assembly, transport, and final installation



## Hand Methods

- A Luna OBR 4600 is being used to take measurements of fiber connections, return losses, distance measurements.
- Using standard Luna software each measurement run must be hand initiated, measurements pulled from the front panel program, (picking peaks, regions of interest, power calculation, deltas, etc.), a very LABOR INTENSIVE process when doing many channels



## Using the Luna OBR 4600 for Gap Measurements


- The Luna OBR 4600 is used for high resolution scans of an AOC probe to the a surface of interest.
- An AOC probe can have up 144 individual probe points
- To scan all 144 points, make measurements of distances and record is not practical to do by hand.
- An automated method has been developed using the Luna OBR, high count fiber optic switches, a software development kit (SDK) from Luna, and custom LabVIEW software to tie it altogether.




# Standard Luna software and OBR 4600

Two separate scans of an AOC probe point with no changes to surface location.

Zoomed to the entry of the AOC probe and the return from the surface.



# Compare two scans – unshifted probe/surface




Top Graph is zoomed to the AOC probe and surface return region.

Bottom Graph is the region of the AOC probe entry illustrating jitter between successive scans with no changes in the setup




This graph again shows the jitter between two scans but at the probe surface.



**Nevada National Security Site**


Managed and Operated by National Security Technologies, LLC

# Compare two scans – shifted surface/probe



The original scan shown in blue is the same as the previous graphs, The scan in red shows the surface has shifted.

The graph below shows the probe to surface has shifted by about 36 ps.



**Nevada National Security Site**

Managed and Operated by National Security Technologies, LLC


# An automated method of scanning and measuring

- A method to quickly (relative to hand solutions) to take measurements without disconnecting, cleaning, and re-connecting, fibers for each probe.






# Luna Gap Measurement Layout



The higher 30 meter scan range can be used since the system will be close to the assembly.


Still keep all fiber path lengths to minimum, just the switching hardware paths consume 10 meters.

## Portable Rack-Mount 144 channel Luna scanning equipment.



AOC probe mounted with a test surface..

# Luna Gap Measurement Control Panel



# Features of Measurement Program

Note: Time(ns) is Two-Way

## Analyze Runs

Run X Ports(pS)	Run Y Ports(pS)	Matched Diff (pS)
A01 583.39	A01 615.83	A01 -32.44
A02 586.25	A02 620.29	A02 -34.04
A03 576.19	A03 608.04	A03 -31.85
A04 581.74	A04 617.57	A04 -35.83
A05 576.52	A05 611.38	A05 -34.86
A06 583.07	A06 619.69	A06 -36.62
A07 586.84	A07 622.84	A07 -36.00
A08 574.58	A08 609.36	A08 -34.78
A09 578.70	A09 614.95	A09 -36.25
A10 576.46	A10 612.07	A10 -35.61
A11 591.18	A11 625.05	A11 -33.87
A12 592.06	A12 623.76	A12 -31.70
B01 575.82	B01 605.20	B01 -29.38


Run03 Description

No Washers

Run02 Description

Single Washer

## Run 02 VP0004 A04



**Nevada National Security Site**

Managed and Operated by National Security Technologies, LLC




## Setup for performing Path Analysis

- Use the Luna OBR 4600 with a 1 X n (n=128, 256) FO switching hardware with each switch output connected to a probe illuminator port of the NSTec MPDV.
- The probe send/receive port can be switched between the normal circulator path and the probe illuminator port.
- The extended range scan must be used since the path will be greater than 30 meters, but should be enough resolution to gather all the information needed.
- A permanent installation of a Luna switching matrix can be connected to the MPDV probe illuminator ports. No connection or disconnection of fibers will be required to take measurements and do verification of the entire light path from the MPDV rack to the surface.




# Luna Probe Verification




# Luna Probe Verification Layout (256 channels)

MPDV Extended Range  
Verification Program




# Luna Probe Verification Issues

- Lots of information to gather, analyze, and archive.
- Will require software to automate the procedure of finding all regions of interest, do reflection, power loss, etc., measurements.
- Do we need a database server to tie all of the systems together for a central repository of data and common analysis?
- This is a work in progress and ideas and methods are still in development.





# Sample Scans



**Nevada National Security Site**

Managed and Operated by National Security Technologies, LLC

# Auto-tuning (the Holy Grail)

- What information can be gathered from the extended Luna scans to feed back to the MPDV controller?
- Don't have enough information or experience to answer exactly how auto-tuning will be done, although all of the hooks exists or will be available. This will take some development planning and effort.

